

**Sensor-Interface with USB**

**Type LCV-USB**

- Supply via USB
- Up to 16bit resolution
- Input for mV, V and mA
- Fast measurement of 5000/sec. Peak from sensor
- Calibration and control lock-on via software
- Integrable in many sensors by SMD- miniaturization



The sensor interface LCV-USB is inserted between sensor and PC.

Thus analog sensor signals with up to 16bit resolution are digitized.

With the high dynamics of 5000 measurements/sec. fastest measuring tasks are realizable. \*

The measured values are transferred and visualized by the software via the USB interface.

If 100% calibration control is integrated in the sensor (see data sheet), an automatic calibration can be accomplished, which is auditable at any time (monitoring of the measuring chain).

3 different sensors are intended for the connection:

USB-DMS      Supply 4V max: 20mA  
                  Signal: 0,35 – 3,2mV/V

USB-U5        Supply 12V max: 80mA  
                  Signal: 0-1V ... 0-±5V

USB-I<sub>mA</sub>      Supply 12V max: 80mA  
                  Signal: 0 – 20mA / 4 - 20mA  
                  (Option: 10 ±10mA 12 ±8mA...)

AT USB-I<sub>mA</sub> 2 or 3-wire connection is possible, usual market sensors can be adapted.

At USB-I<sub>mA</sub>, 2 or 3-wire connection is possible, commercially available sensors can be adapted. The practical housing with a high level of protection allows fast fixation by a screwing clamp. In larger sensors, the circuit board module can be integrated as well.

Type	LCV-USB-DMS	LCV-USB-U5	LCV-USB-I <sub>mA</sub>
Art. no.	108368	108369	108370

**TECHNICAL DATA:**

Supply	from USB	4-6V DC max 350mA
Supply for sensor	DMS U5 I <sub>mA</sub>	4V max. 20mA 12V max. 80mA 12V max. 80mA
Measured values	DMS U5 I <sub>mA</sub>	0-±3mV/V = 32768 ±30000 bits 0-±5V = 32768 ±25000 bits 0- 20mA = 32768 +20000 bits
Resolution	DMS U5 I <sub>mA</sub>	1mV/V = 10000 bits 1V = 5000 bits 1mA = 1000 bits
Zero point	DMS / U5 / I <sub>mA</sub>	32768 bits
Input resistance	DMS U5 I <sub>mA</sub> load:	200 G Ohm 1,3 M Ohm 62 Ohm
Measuring rate		5000 meas/sec *
Temperature drift		4bit / 10k
Linearity error		±5bit
Accuracy		±5bit

Further	
Max. cable length to sensor	3m
USB cable length max.	5m
Nominal temperature range	10...40 °C
Service temperature range	0...50 °C
Storage temperature range	-10...70 °C

\* limited to 200 meas./sec at operation of the LCV-USB-VS with Windows.